



**MATERIAL SAFETY DATA SHEET**

**MSDS# 0100**

**SECTION 1**

QUADRANT EPP  
2120 FAIRMONT AVENUE  
P.O. BOX 14235  
READING, PA. 19612-4235

TELEPHONE NUMBERS:  
PRODUCT INFORMATION(Quadrant EPP ) -  
610-320-6600  
TRANSPORTATION EMERGENCY (CHEMTREC) -  
800-424-9300

MATERIAL IDENTIFICATION

PRODUCT NAME: **QUADRANT NYLON 101, 103, 105**

CHEMICAL NAME: **POLYHEXAMETHYLENE ADIPAMIDE - NYLON 66**

CAS NO.: **32131-17-2 (BASE POLYMER)**

PRODUCT USE: **ENGINEERING THERMOPLASTIC STOCK SHAPE FOR  
SUBSEQUENT FABRICATION.**

TSCA INVENTORY STATUS: **ALL REPORTABLE INGREDIENTS ARE LISTED IN  
THE TSCA CHEMICAL SUBSTANCE INVENTORY.**

---

**SECTION 2**

HAZARDOUS INGREDIENTS (ADDITIVES NOT HAZARDOUS BY 29 CFR 1910.1200)

IDENTITY	CAS#	CONCENTRATION	TVL (TWA)
<b>*Stabilizers</b>		<b>&lt;11</b>	

---

**SECTION 3**HEALTH HAZARD DATA

ACUTE OR IMMEDIATE EFFECTS: ROUTES OF ENTRY AND SYSTEMS.

INGESTION: **NOT A PROBABLE ROUTE OF EXPOSURE.**

SKIN: **MOLTEN NYLON CAUSES THERMAL BURNS.**

EYE: **MECHANICAL IRRITATION ONLY.**

INHALATION: **SHAPES NOT RESPIRABLE.**

---

**SECTION 4**EMERGENCY FIRST AID

- If exposed to fumes from overheating, move to fresh air. Consult a physician if symptoms persist.
- Wash skin with soap and plenty of water.
- Flush eyes with water. Consult a physician if symptoms persist.
- If molten polymer contacts skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain medical attention to thermal burn.

CHRONIC EFFECTS: **NONE KNOWN.**

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY THIS MATERIAL: **NONE KNOWN.**

---

## SECTION 5

FIRE AND EXPLOSION HAZARD DATA

FLASH IGNITION TEMPERATURE: **752 F./400 C.** METHOD: **ASTM D-1929**

UNUSUAL FIRE, EXPLOSION HAZARDS: **NONE KNOWN.**

HAZARDOUS DECOMBUSTION PRODUCTS: **AT TEMPERATURES ABOVE 644 F. /340 C., HEAVY FUMING, CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN OXIDES AND HYDROGEN CYANIDE (AT TEMPERATURES ABOVE 660 F./349 C. WILL OCCUR.**

SPECIAL FIRE FIGHTING INSTRUCTIONS: **FIRE FIGHTERS AND OTHERS EXPOSED TO PRODUCTS OF COMBUSTION SHOULD WEAR FULL PROTECTIVE CLOTHING INCLUDING SELF-CONTAINED BREATHING APPARATUS. FIRE FIGHTING EQUIPMENT SHOULD BE THOROUGHLY DECONTAMINATED AFTER USE.**

EXTINGUISHING MEDIA: **WATER SPRAY OR ANY CLASS A EXTINGUISHING AGENT.**

- > PHYSICAL HEALTH HAZARDS:  
**DUST MAY FORM EXPLOSIVE MIXTURES WITH AIR. AVOID DUST FORMATION AND CONTROL IGNITION SOURCES. ALL PLASTIC DUST PARTICLES SUSPENDED IN AIR ARE COMBUSTIBLE AND MAY BE EXPLOSIVE. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND OTHER IGNITION SOURCES. PREVENT DUST ACCUMULATIONS AND DUST CLOUDS. EMPLOY GROUNDING, VENTING, AND EXPLOSIVE RELIEF PROVISIONS IN ACCORDANCE WITH ACCEPTED ENGINEERING PRACTICES AND NFPA PROVISIONS IN ANY PROCESS CAPABLE OF GENERATING DUST AND/OR STATIC ELECTRICITY. EXPLOSION HAZARDS APPLY ONLY TO DUSTS, NOT GRANULAR FORMS OF THIS PRODUCT. SEE ALSO SPECIAL PRECAUTIONS SECTION BELOW.**

---

SECTION 6ACCIDENTAL RELEASES

SPILL OR RELEASE: **CLEAN UP BY VACUUMING OR SWEEPING TO PREVENT FALLS.**

---

## SECTION 7

STORAGE CONDITIONS

**Dry storage. Keep containers closed to prevent contamination.**

---

## SECTION 8

PROTECTION INFORMATION

**EYE: Safety glasses are recommended to prevent particulate matter from entering eyes while grinding or machining.**

**SKIN: Protective gloves are required when handling hot polymer. Also, long sleeve cotton shirt and long pants if handling molten polymer.**

**VENTILATION: Local exhaust at processing equipment to keep particulates below 15 mg/m<sup>3</sup>, the OSHA limit for nuisance dusts. Grinding and machining of parts should be reviewed to assure that particulate levels are kept at recommended standards.**

**RESPIRATOR: None under normal processing, if ventilation is adequate.**

---

## SECTION 9

PHYSICAL/CHEMICAL DATA

**APPEARANCE: STOCK SHAPE MAY BE ROD, PLATE, TUBE, OR STRIP FORM.**

**ODOR: ESSENTIALLY ODORLESS.**

**MELTING POINT: 250 - 265 C./ 482 - 509 F.**

**SOLUBILITY IN WATER: INSOLUBLE.**

**VOLATILE CONTENT %: <1%**

**SPECIFIC GRAVITY: 1.13 - 1.15**

- > PRECAUTIONS FOR REPAIR & MAINTENANCE OF CONTAMINATED EQUIPMENT:
- > ELIMINATE IGNITION SOURCES:
- > **TRANSFER FROM STORAGE WITH A MINIMUM AMOUNT OF DUSTING. GROUND**
- > **ALL TRANSFER, BLENDING, AND DUST COLLECTING EQUIPMENT TO PREVENT**

- > STATIC SPARKS IN ACCORDANCE WITH NFPA 70 "NATIONAL ELECTRIC
- > CODE". REVIEW AND COMPLY WITH ALL RELEVANT NFPA PROVISIONS,
- > INCLUDING BUT NOT LIMITED TO NFPA 484 AND NFPA 654 RELATED TO
- > COMBUSTIBLE DUST HAZARDS. REMOVE ALL IGNITION SOURCES FROM
- > MATERIAL HANDLING, TRANSFER, AND PROCESSING AREAS WHERE DUST MAY
- > BE PRESENT. LOCAL EXHAUST VENTILATION SHOULD BE PROVIDED IN WORK
- > AREA.

---

## SECTION 10

### HAZARDOUS REACTIVITY

STABILITY AT ROOM TEMPERATURE: **STABLE.**

MATERIALS TO AVOID: **STRONG ACIDS AND OXIDIZING AGENTS.**

CONDITIONS TO AVOID: **HEATING ABOVE 340 C/644 F.**

---

## SECTION 11

### TOXICOLOGICAL INFORMATION

CHRONIC TOXICITY: **NYLON 101 DOES NOT APPEAR TO POSSESS ANY TOXICOLOGICAL PROPERTIES.**

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: **THERMAL DECOMPOSITION PRODUCTS OF NYLON HAVE BEEN REPORTED TO BE IRRITATING TO THE MUCUS MEMBRANES AND RESPIRATORY TRACT.**

CARCINOGENICITY: **NONE KNOWN.**

---

## SECTION 12

### ECOLOGICAL INFORMATION

**AQUATIC TOXICITY: Toxicity is expected to be low based on insolubility of polymer in water.**

---

## SECTION 13

DISPOSAL

**SPILL OR RELEASE:** Clean up by vacuuming or wet sweeping to minimize dust exposure.

**WASTE DISPOSAL:** Recycling is encouraged, Landfill or incineration in compliance with Federal, State, and Local regulations.

---

## SECTION 14

TRANSPORT INFORMATION

DOT HAZARD CLASS: **NA**  
SHIPPING NAME: **NA**

---

## SECTION 15A

**REGULATORY INFORMATION**SECTION 313 SUPPLIER NOTIFICATION:  
(SARA TITLE III-TOXIC CHEMICALS LIST)

This product contains no known toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372.

STATE RIGHT TO KNOW LAWS

No substances on the state hazardous list, for the states indicated below, are used in the manufacture of products on this Material Safety Data Sheet, with the exceptions indicated. While we do not specifically analyze these products, or the raw materials used in their manufacture, for substances on various state hazardous substances lists, to the best of our knowledge the products on this Material Safety Data Sheet contain no such substances except for those specifically listed below:

PENNSYLVANIA:

SUBSTANCES ON THE PENNSYLVANIA HAZARDOUS SUBSTANCES LIST PRESENT AT A CONCENTRATION OF 1% OR MORE: **NONE KNOWN.**

SUBSTANCES ON THE PENNSYLVANIA SPECIAL HAZARDOUS SUBSTANCES LIST PRESENT AT A CONCENTRATION OF 0.01% OR MORE: **NONE KNOWN.**

CALIFORNIA PROPOSITION 65:

SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER: **NONE KNOWN.**

SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: **NONE KNOWN.**

**SECTION 15B  
LABELING INFORMATION**

**HMIS RATING**

Health	0
Flammability	1
Reactivity	0
PPE	A
#Acute <input type="checkbox"/> *Chronic <input type="checkbox"/>	

**SECTION 16**

MISCELLANEOUS INFORMATION

Issued by: Richard Frey, SHE Manager, NA

Issued: October 28, 2008

Supersedes: January 31, 2008

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is, to the best knowledge and belief of Quadrant EPP, accurate and reliable. Such information is offered solely for your consideration, investigation and verification, and it is not suggested or guaranteed that the hazard precautions or procedures mentioned are the only ones that exist. Quadrant EPP makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility therefor.

\* = Components for Nylon 103 & 105

NA = Not applicable

NE = Not established.

> = New or revised information in this section when " > " appears in the left margin.

**END OF MSDS**