

The heavy-duty, waterproof and graffiti resistant polymer sheet

King Plasti-Bal® is designed for commercial and industrial architectural applications. The heavy-duty, waterproof and graffiti resistant polymer sheet is offered in five matte gloss finished colors. Additional colors and designer textures are available upon request. All of the King Plasti-Bal colors are environmentally friendly, which will allow you to qualify for LEED® rating points. The raw materials used to make King Plasti-Bal are FDA and USDA approved.

King Plasti-Bal is upgradable to King MicroShield® with an exclusive antimicrobial additive from Biosafe®, the latest technology for protecting the product surface against stain and odor causing bacteria, algae and fungi.*

King Plasti-Bal is upgradable with King FlameShield, for ASTM E-84 Class A or B Flame/Smoke Compliance and CAN/ULC-S102 for Canadian Compliance.

For more information about King MicroShield and King FlameShield, please visit www.kingplastic.com

KING
PLASTI-BAL®

Applications

- Benches
- Lockers
- Privacy Screens
- Restroom Partitions
- Shower Enclosures

Specifications

Standard Sheet Size

in: 1" x 55.5" x 144"

mm: 25.4mm x 1409.7mm x 3657.6mm

Standard Gauge

in: .950" - .999"

mm: 24.13mm - 25.4mm

Approximate Weight

lbs: 270 lbs

kg: 122.5kg

Tolerance information:

Length and width plus only at room temperature

Custom sheet sizes, gauges, and colors available

Standard Colors



Ebony




Brownstone



Sierra Brown



Deckhand Gray



Island Sand

Note: Color accuracy can vary considerably on computer monitors and printers. Please consult your distributor for a product sample before making critical color choices.

Active ingredient (Biosafe®).....antimicrobial siloxane EPA Reg. No. 83019-1
*For bacteriostatic, fungistatic, & algistatic properties. This product is exempt from registration under 40 CFR 152.25(a). King MicroShield® effectiveness verified by ISO and ASTM standards. This product does not protect users or others from disease-causing bacteria. Always clean this product thoroughly after use.

Biosafe® is a registered trademark of BIOSAFE, Inc.: Patent number 7,851,653 and 7,858,141.

Properties	Units	ASTM	Nominal Values
Density	g/cc	D1505	0.96
Tensile Strength @ Yield	psi	D638	>4,100
Tensile Modulus	psi	D638	255,000
Elongation @ Yield	%	D638	9.8
Elongation @ Break	%	D638	>600
Flexural Modulus	psi	D790	185,000
Flexural Stress @ 5% Strain	psi	D790	3,810
Compressive Properties 10% Strain	psi	D695	4,950
Durometer	Shore D	D2240	68
Tensile Impact	ft.lbs./in.2	D1822	115
Izod Impact Resistance	ft.lbs./in.2	D256	1.1
Brittleness Temp.	°C (°F)	D746	<-76°C (<-105°F)
Vicat Softening	°C (°F)	D1525	123°C (253°F)
Heat Deflection Temp. 66 psi	°C (°F)	D648	75°C (167°F)
Screw and Nail Withdrawal	lbs	D1761	657 & 63
Flammability	Rating	UL94	HB

All values are determined on specimens prepared according to ASTM.

Nominal values should not be interpreted as specifications.

King Plasti-Bal® is made entirely from FDA and made with USDA approved materials.

King Plasti-Bal® meet ASTM D4976.



King Plastic Corporation
Our Innovation. Your Imagination.™

1100 N. Toledo Blade Blvd. | North Port, FL 34288 USA
P: 941.493.5502 | F: 941.497.3274 | www.kingplastic.com